



recessed spot
Artikel-Nr. 13 14 1033

Licht.
 Für Generationen.



Distance (m)	Beam Diameter (m)	Luminous Flux (lm)
1.0 m	0.710.7	1173.2
2.0 m	1.411.4	293.3
3.0 m	2.112.0	130.4
4.0 m	2.812.7	73.3
5.0 m	3.513.4	46.9

recessed spot, chrome. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: Plug&Play 350mA, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Cast iron / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 6 W, Luminous flux: 640.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 38.0 °, Adjustability: swivelling, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A, Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

Artikel-Nr.	13 14 1033	Applications
price	75.90 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 14:04	GASTRONOMY

colour of light	3000 K
Colour	chrome
Radiation angle	38 °
amount of light sources /	1 Qty
material	Cast iron / Aluminium / Glass
version	Plug&Play
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other
Outer diameter	88 mm
Built-in diameter	68 mm

Built-in depth	50 mm
current	350 mA
Luminous flux	640 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Circlip	without circlip
Adjustability	swivelling
Energy efficiency class	A++ to A
Swivel angle	25 °
circuit type secondary side	series conduction