


recessed spot

Artikel-Nr. 88647074



recessed spot, weiß. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 27W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 3.286lm, Farbtemperatur: 3500K, Colour of light: white, Radiation angle: 12°, Adjustability: rotating and swivelling, With operating gear, Type of dimming: switchable, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	88647074	Applications	
Stand:	25.11.2020 15:59	SHOP RETAIL EDUCATION CULTURE	
colour of light	3500	Built-in diameter	168 mm
Colour	white	Built-in depth	172 mm
amount of light sources / fittings	1 Qty	voltage	230V AC 50Hz
material	Aluminium	IP protection class	IP20
Power	27 W	Protection class	II
Lamp type	LED	Voltage type	AC
Colour rendering	CRI > 80	Adjustability	rotating and swivelling
Type of dimming	switchable	Swivel angle	35 °
Outer diameter	180 mm	circuit type secondary side	parallel conduction