



recessed spot

**Artikel-Nr. 12252023**



1.0 m	0.8 0.7	569.5
2.0 m	1.6 1.4	142.4
3.0 m	2.4 2.1	63.3
4.0 m	3.2 2.8	35.6
5.0 m	4.0 3.6	22.8
	Ø (m)	E0(0°) [lx]

recessed spot, chrom, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 3W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 290lm, Farbtemperatur: 2700K, Colour of light: white, Radiation angle: 38°, Adjustability: swivelling, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>12252023</b>	<b>Applications</b>
<b>Stand:</b>	26.11.2020 02:56	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY   GASTRONOMY

colour of light	2700
Colour	chrome
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
version	Plug&Play
Power	3 W
Lamp type	LED
Colour rendering	CRI > 80
Built-in diameter	68 mm

Built-in depth	40 mm
Current	350 mA
Luminous flux	290 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
length	82 mm
Width	82 mm
Swivel angle	30 °
circuit type secondary side	series conduction