



recessed spot

Artikel-Nr. 13189023



1.0 m	0.7 0.7	1173.2
2.0 m	1.4 1.4	283.3
3.0 m	2.1 2.0	130.4
4.0 m	2.8 2.7	73.3
5.0 m	3.5 3.4	46.9
	Ø (m)	E0(0°) [lx]

recessed spot, chrom. In a compact design, for installation in tool-less rapid assembly systems. version: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Cast aluminium / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 680lm, Colour temperature: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: rotating and swivelling, without operating, Type of dimming: switchable, . Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

Artikel-Nr.	13189023
Stand:	21.04.2021 21:19

colour of light	3000 K
Colour	chrome
length	88 mm
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Cast aluminium / Aluminium / Glass
version	Plug&Play
Power	6 W
Lamp type	LED
shipping	ohne Sprengring
Colour rendering	CRI > 80
Type of dimming	switchable

Built-in diameter	70 mm
Built-in depth	50 mm
Current	350 mA
Luminous flux	680 lm
IP protection class	IP20
Protection class	III
Adjustability	rotating and swivelling
length	88 mm
Width	88 mm
Rotation angle	355 °
Swivel angle	25 °
circuit type	series conduction