


## LED-Anbaudownlight IP44

**Artikel-Nr. 88521693**

LED-Anbaudownlight IP44, struktursilber, round. Surface mounting, Ceiling-mounted. LED-Anbauleuchte, schaltbar. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP44, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 10W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 900lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 85°, With operating gear, . This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>88521693</b>
<b>Stand:</b>	11.02.2021 19:57

colour of light	3000
Colour	silver
Radiation angle	85 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
Power	10 W
Lamp type	LED
Colour rendering	CRI > 80

Outer diameter	90 mm
voltage	230V AC 50Hz
Luminous flux	900 lm
IP protection class	IP44
Protection class	I
Height	125 mm
circuit type secondary side	parallel conduction