


LED-Einbaudownlight
Artikel-Nr. 40515073



LED-Einbaudownlight, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 500 mA, Power: 14W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 1.050lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 60°, Adjustability: not adjustable, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	40515073
price	94.00 €
Stand:	20.03.2020 09:32

colour of light	3000 K
Colour	white
Radiation angle	60 °
amount of light sources / fit-	1 Qty
material	Aluminium / Plastic
Power	14 W
Lamp type	LED
Colour rendering	CRI > 80
Outer diameter	159 mm

Built-in diameter	125 mm
Built-in depth	90 mm
current	500 mA
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
circuit type secondary side	series conduction