


LED-Einbaudownlight
Artikel-Nr. 12090073

Licht.
 Für Generationen.



LED-Einbaudownlight, white, round. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 3 W, Luminous flux: 300.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 150.0 °, Adjustability: not adjustable, With operating gear: No, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12090073	Applications
price	34.90 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 11:56	GASTRONOMY

colour of light	3000 K
Colour	white
Radiation angle	150 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	3 W
Lamp type	LED
Colour rendering	CRI > 80
Outer diameter	68 mm

Built-in diameter	60 mm
Built-in depth	16.5 mm
current	350 mA
Luminous flux	300 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
circuit type secondary side	series conduction