


## LED-Einbau- / Anbaudownlight X-FLAT

## Artikel-Nr. 12164023



LED-Einbau- / Anbaudownlight, round. In a compact design, for installation in tool-less rapid assembly systems. Diese Leuchte ist sowohl als Einbau- (Lochausschnitt: 56 mm, Einbautiefe: 3,5 mm, Aufbauhöhe: 2,2 mm), als auch als Anbau-leuchte (Gesamthöhe: 5,9 mm) durch mitgeliefertes Anbaugehäuse zu verwenden. Außenkante nickel matt, magnetisch befestigte Blende in Farbton laut Artikeltabelle. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 12V , Power: 2,6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 180lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 120°, Adjustability: not adjustable, without operating, .

<b>Artikel-Nr.</b>	<b>12164023</b>	<b>Applications</b>
<b>price</b>	42.90 €	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY
<b>Stand:</b>	19.03.2020 10:45	GASTRONOMY

colour of light	3000 K
Radiation angle	120 °
amount of light sources / fit-	1 Qty
material	Aluminium / Steel / Plastic
Power	2,6 W
Lamp type	LED
shipping	inkl. 2.000 mm Anschlusslei-
Colour rendering	CRI > 85
Outer diameter	75 mm
Built-in diameter	56 mm

Built-in depth	3.5 mm
voltage	12V
Luminous flux	180 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
Height	5.9 mm
circuit type secondary side	parallel conduction