


recessed spot

Artikel-Nr. 89154035

recessed spot, weiß. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 27W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 2.832lm, Farbtemperatur: 3500K, Colour of light: white, Radiation angle: 60°, Adjustability: rotating and swivelling, With operating gear, .

Artikel-Nr. 89154035
Stand: 16.02.2021 04:28

Radiation angle	60 °
colour of light	3500
Colour	weiß
Luminous flux	2,832 lm
material	Aluminium
Power	27 W
System output	27 W
Built-in diameter	120 mm

Built-in depth	30 mm
voltage	230V AC 50Hz
circuit type secondary side	parallel conduction
IP protection class	IP20
Protection class	II
Voltage type	AC
Adjustability	rotating and swivelling
Height	235 mm