


LED-Einbaudownlight
Artikel-Nr. 12027153

Licht.
 Für Generationen.



LED-Einbaudownlight, titanium, round. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Cast iron / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 12V, Power: 2 W, Luminous flux: 125.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 45.0 °, Adjustability: not adjustable, With operating gear: No, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12027153	Applications
price	53.40 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 16:13	GASTRONOMY

colour of light	3000 K
Colour	alu
Radiation angle	45 °
amount of light sources /	1 Qty
material	Cast iron / Plastic
Power	2 W
Lamp type	LED
shipping	inkl. 2.000 mm Anschluss-
Colour rendering	CRI > 80
Outer diameter	70 mm

Built-in depth	14 mm
voltage	12V
Luminous flux	125 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
circuit type secondary side	parallel conduction