




LED-Einbaudownlight REEP
Artikel-Nr. 12342553



LED-Einbaudownlight REEP, white/black. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 700 mA, Power: 11W, amount of light sources / fittings: 5.0 Stk, Luminous flux: 810lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 13°, Adjustability: not adjustable, without operating, Type of dimming: other, .

| | |
|-----------------------|------------------|
| Artikel-Nr. | 12342553 |
| price | 118.80 € |
| Stand: | 01.09.2020 22:17 |
| Discount group | Discount group 1 |

| | |
|------------------------------------|---------------------|
| colour of light | 3000 K |
| Colour | white/black |
| Radiation angle | 13 ° |
| amount of light sources / fittings | 5 Qty |
| material | Aluminium / Plastic |
| version | Plug&Play |
| Power | 11,5 W |
| Lamp type | LED |
| Colour rendering | CRI > 80 |
| Type of dimming | other |
| Built-in width | 180 mm |

| | |
|-----------------------------|-------------------|
| Built-in length | 50 mm |
| Built-in depth | 59 mm |
| Current | 700 mA |
| Luminous flux | 810 lm |
| IP protection class | IP20 |
| Protection class | III |
| Voltage type | DC |
| Adjustability | not adjustable |
| Length | 190 mm |
| Width | 54 mm |
| circuit type secondary side | series conduction |