


LED-Anbaudownlight IMPLEMENT, 2-fach, dimmbar

**Artikel-Nr. 12393173**

Licht.  
Für Generationen.



LED-Anbaudownlight IMPLEMENT, 2-fach, dimmbar, rectangular. Surface mounting, Ceiling-mounted. Leuchte inkl. Konverter für 230 V-Netzspannung, Phasenabschnitt. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 2 x 8,9 W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 1460.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 37.0 °, Adjustability: not adjustable, With operating gear: Yes, Type of dimming: Phase cut-off, Energy efficiency class: A++ to A,

<b>Artikel-Nr.</b>	<b>12393173</b>
<b>price</b>	289.00 €
<b>Stand:</b>	28.08.2019 09:55

colour of light	3000 K
Radiation angle	37 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
Lichtstrom	2 x 730 lm
Power	2 x 8,9 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss
Colour rendering	CRI > 90
Type of dimming	Phase cut-off

voltage	230V AC 50Hz
Luminous flux	1,460 lm
IP protection class	IP20
Protection class	I
Voltage type	AC
Adjustability	not adjustable
Energy efficiency class	A++ to A
Height-depth	115.0 mm
circuit type secondary side	parallel conduction