




recessed spot

**Artikel-Nr. 12476173**

Licht.  
Für Generationen.



recessed spot, white, round. In a compact design, for installation in tool-less rapid assembly systems. Wird die Leuchte gedimmt, verringert sich die Farbtemperatur. Einbaustrahler geeignet zur direkten Montage auf normalentflammbaren Baustoffen. Wärmedämmung zulässig. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 5,5 W, Luminous flux: 500.0 lm, colour of light: 3000 to 1800 K, Radiation angle: 36.0 °, Adjustability: swivelling, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>12476173</b>	<b>Applications</b>
<b>price</b>	59.60 €	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY
<b>Stand:</b>	27.08.2019 10:48	GASTRONOMY

colour of light	3000 - 1800 K
Colour	white
Radiation angle	36 °
amount of light sources /	1 Qty
material	Aluminium / Steel / Plastic
version	Plug&Play
Power	5,5 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other
Outer diameter	95 mm

Built-in diameter	83 mm
Built-in depth	38 mm
current	350 mA
Luminous flux	500 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Energy efficiency class	A++ to A
Swivel angle	25 °
circuit type secondary side	series conduction