



LED-Einbaustrahler BB15, dimmbar, mit Phasenabschnitt-Konverter und Anschlussbox



1.0 m	0.7 0.6	1184.2
2.0 m	1.4 1.3	296.1
3.0 m	2.1 1.9	131.6
4.0 m	2.8 2.5	74.0
5.0 m	3.5 3.1	47.4
Ø (m)		E0(0°) [lx]

LED-Einbaustrahler BB15, dimmbar, mit Phasenabschnitt-Konverter und Anschlussbox, weiß. In a compact design, for installation in tool-less rapid assembly systems. Set inkl. Konverter für 230 V-Netzspannung, Phasenabschnitt, Maße Konverter: L 110 x B 50 x H 19 mm. Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 640lm, Colour temperature: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: not adjustable, With operating gear, Type of dimming: Phase cut-off, .

Artikel-Nr.	39475073	Applications
Stand:	26.11.2020 12:10	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	3000
Colour	white
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Stainless steel / Aluminium / Glass
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	Phase cut-off

Outer diameter	82 mm
Built-in diameter	68 mm
Built-in depth	45 mm
voltage	230V AC 50Hz
Luminous flux	640 lm
IP protection class	IP54*
Protection class	II
Voltage type	AC
Adjustability	not adjustable
circuit type secondary side	parallel conduction