


LED-Anbaudownlight, IP54
Artikel-Nr. 12076173

Licht.
 Für Generationen.



LED-Anbaudownlight, IP54, white, square. Surface mounting, Ceiling-mounted. . Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 7 W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 450.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 30.0 °, Adjustability: not adjustable, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12076173
price	162.60 €
Stand:	28.08.2019 10:06

colour of light	3000 K
Colour	white
Radiation angle	30 °
amount of light sources /	1 Qty
material	Aluminium / Glass
Power	7 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss
Colour rendering	CRI > 80
Type of dimming	switchable
voltage	230V AC 50Hz

Luminous flux	450 lm
IP protection class	IP54
Protection class	I
Voltage type	AC
Adjustability	not adjustable
Energy efficiency class	A++ to A
Length	70 mm
Width	70 mm
Height-depth	85.0 mm
circuit type secondary side	parallel conduction