


recessed spot

Artikel-Nr. 12632073

Licht.
Für Generationen.



recessed spot, white. In a compact design, for installation in tool-less rapid assembly systems. Montage nur zzgl. Einputz- oder Einbaurahmen 82030170 oder 82032170 möglich.<P/></TEXT>. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 500 mA, Power: 8,9 W, Luminous flux: 950.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 34.0 °, Adjustability: rotating and swivelling, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A,

| | | |
|--------------------|------------------|---|
| Artikel-Nr. | 12632073 | Applications |
| price | 69.90 € | HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY |
| Stand: | 27.08.2019 15:16 | GASTRONOMY |

| | |
|---------------------------|---------------------|
| colour of light | 3000 K |
| Colour | white |
| Radiation angle | 34 ° |
| amount of light sources / | 1 Qty |
| material | Aluminium / Plastic |
| Power | 8,9 W |
| Lamp type | LED |
| Colour rendering | CRI > 90 |
| Type of dimming | other |
| Outer diameter | 68 mm |

| | |
|-----------------------------|-------------------------|
| Built-in depth | 94 mm |
| current | 500 mA |
| Luminous flux | 950 lm |
| IP protection class | IP20 |
| Protection class | III |
| Voltage type | DC |
| Adjustability | rotating and swivelling |
| Energy efficiency class | A++ to A |
| Swivel angle | 20 ° |
| circuit type secondary side | series conduction |