


LED-Einbaudownlight, IP54

Artikel-Nr. 12267073

LED-Einbaudownlight, IP54, weiß, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54*, Protection class: (EN 61140) III, current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 540lm, Farbtemperatur: 2700K, Colour of light: white, Radiation angle: 38°, Adjustability: not adjustable, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr. 12267073
Stand: 21.04.2021 18:07

colour of light	2700 K
Colour	white
length	82 mm
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
version	Plug&Play
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Built-in diameter	68 mm

Built-in depth	58 mm
Current	350 mA
Luminous flux	540 lm
IP protection class	IP54*
Protection class	III
Circlip	without circlip
Adjustability	not adjustable
length	82 mm
Width	82 mm
circuit type	series conduction