


recessed spot

Artikel-Nr. 89151035



recessed spot, white. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 27W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 2.756lm, Farbtemperatur: 3500K, Colour of light: white, Radiation angle: 12°, Adjustability: rotating and swivelling, With operating gear, .

Artikel-Nr.	89151035	Applications
price	349.00 €	SHOP RETAIL EDUCATION CULTURE
Stand:	19.03.2020 12:03	

Radiation angle	12 °
colour of light	3500 K
Colour	weiß
Luminous flux	2,756 lm
material	Aluminium
Power	27 W
System output	27 W
Built-in diameter	120 mm

Built-in depth	30 mm
voltage	230V AC 50Hz
circuit type secondary side	parallel conduction
IP protection class	IP20
Protection class	II
Voltage type	AC
Adjustability	rotating and swivelling