


Smart Light Solutions Downlightset, V4A, DALI, IP54, 2-fach  
**Artikel-Nr. 13175423**

Licht.  
 Für Generationen.



Smart Light Solutions Downlightset, V4A, DALI, IP54, 2-fach, stainless steel. . Weißlicht-Set inkl. 1 x Konverter für 230 V-Netzspannung, DALI dimmbar, Maße Konverter: L 110,5 x B 52 x H 22 mm, 2 x LED-Einbaudownlights, 2 x Plug&Play-Leitung (je 2.000 mm). material: Stainless steel / Aluminium / Plastic / Glass, IP protection class: according to DIN EN 60529 IP54\*, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 2 x 6 W, amount of light sources / fittings: 2.0 Stk, Luminous flux: 1280.0 lm, Radiation angle: 38.0 °, Type of dimming: DALI, Energy efficiency class: A++ to A,

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>13175423</b>  |
| <b>price</b>       | 245.00 €         |
| <b>Stand:</b>      | 28.08.2019 16:25 |

|                           |                               |
|---------------------------|-------------------------------|
| colour of light           | 3000 K                        |
| Colour                    | stainless steel               |
| Radiation angle           | 38 °                          |
| amount of light sources / | 2 Qty                         |
| material                  | Stainless steel / Aluminium / |
| version                   | Plug&Play                     |
| Lichtstrom                | 2 x 640 lm                    |
| Power                     | 2 x 6 W                       |
| Lamp type                 | LED                           |
| Colour rendering          | CRI > 80                      |

|                             |                     |
|-----------------------------|---------------------|
| Type of dimming             | DALI                |
| Built-in diameter           | 68 mm               |
| Built-in depth              | 45 mm               |
| voltage                     | 230V AC 50Hz        |
| Luminous flux               | 1,280 lm            |
| IP protection class         | IP54*               |
| Protection class            | II                  |
| Circlip                     | without circlip     |
| Energy efficiency class     | A++ to A            |
| circuit type secondary side | parallel conduction |