



recessed spot

Artikel-Nr. 12251023



1.0 m	0.8 0.7	569.5
2.0 m	1.6 1.4	142.4
3.0 m	2.4 2.1	63.3
4.0 m	3.2 2.8	35.6
5.0 m	4.0 3.6	22.8
	Ø (m)	E0(0°) [lx]

recessed spot, chrom, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 3W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 290lm, Farbtemperatur: 2700K, Colour of light: white, Radiation angle: 38°, Adjustability: swivelling, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12251023	Applications
Stand:	26.11.2020 07:03	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	2700
Colour	chrome
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
version	Plug&Play
Power	3 W
Lamp type	LED
Colour rendering	CRI > 80
Outer diameter	82 mm

Built-in diameter	68 mm
Built-in depth	40 mm
Current	350 mA
Luminous flux	290 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Swivel angle	30 °
circuit type secondary side	series conduction