


recessed spot

Artikel-Nr. 18427252

Licht.
Für Generationen.



recessed spot, alu. In a compact design, for installation in tool-less rapid assembly systems. Anschluss an Verteiler 18301000 & 18314000 nur möglich über Systemkabel 18900000 - 18902000. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 12V, Power: 14 W, colour of light: 2000 to 10000 K, Radiation angle: 40.0 °, Adjustability: swivelling, With operating gear: No, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	18427252
price	229.60 €
Stand:	16.07.2019 12:32

colour of light	vitaLED® RGBW
Colour	alu
Radiation angle	40 °
material	Aluminium / Plastic
Power	14 W
Lamp type	LED
Colour rendering	CRI > 80
Built-in diameter	68 mm
Built-in depth	80 mm
voltage	12V

IP protection class	IP20
Protection class	III
Voltage type	DC
Circlip	without circlip
Adjustability	swivelling
Energy efficiency class	A++ to A
Length	82 mm
Width	82 mm
Swivel angle	20 °
circuit type secondary side	parallel conduction