


recessed spot

Artikel-Nr. 88656083



recessed spot, schwarz. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 40W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 4.382lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 12°, Adjustability: rotating and swivelling, With operating gear, Type of dimming: switchable, .

Artikel-Nr.	88656083	Applications
Stand:	25.11.2020 22:56	SHOP RETAIL EDUCATION CULTURE
colour of light	3000	Outer diameter
Colour	black	Built-in diameter
Radiation angle	12 °	Built-in depth
amount of light sources / fittings	1 Qty	voltage
material	Aluminium	IP protection class
Power	40 W	Protection class
Lamp type	LED	Voltage type
Colour rendering	CRI > 80	Adjustability
Type of dimming	switchable	Swivel angle
		circuit type secondary side