


LED-Anbaudownlight, IP54

Artikel-Nr. 12077173

LED-Anbaudownlight, IP54, white, square. Surface mounting, Ceiling-mounted. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 7W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 450lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 120°, Adjustability: not adjustable, With operating gear, Type of dimming: switchable, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12077173
price	143.70 €
Stand:	01.09.2020 15:44
Discount group	Discount group 1

colour of light	3000 K
Colour	white
Radiation angle	120 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
Power	7 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar
Colour rendering	CRI > 80

Type of dimming	switchable
voltage	230V AC 50Hz
Luminous flux	450 lm
IP protection class	IP54
Protection class	I
Voltage type	AC
Adjustability	not adjustable
Length	80 mm
Width	80 mm
Height-depth	80 mm
circuit type secondary side	parallel conduction