


vitaLED®-Einbaustrahler  
**Artikel-Nr. 18448252**



vitaLED®-Einbaustrahler, alu matt. In a compact design, for installation in tool-less rapid assembly systems. Anschluss an Verteiler 18301000 & 18314000 nur möglich über Systemkabel 18900000 - 18902000. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 24V, Power: 12W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 450lm, Farbtemperatur: 2000 bis 10000K, Radiation angle: 60°, Adjustability: swivelling, without operating, . Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

**Artikel-Nr.** 18448252  
**Stand:** 25.11.2020 09:04

colour of light	vitaLED® RGBW
Radiation angle	60 °
amount of light sources / fittings	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	12 W
Lamp type	LED
Colour rendering	CRI > 80
Built-in diameter	75 mm
Built-in depth	100 mm
voltage	24V

Luminous flux	450 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Circlip	without circlip
Adjustability	swivelling
length	90 mm
Width	90 mm
Height	3 mm
Swivel angle	30 °
circuit type secondary side	parallel conduction