




recessed spot

Artikel-Nr. 12461073



recessed spot, weiß, round. In a compact design, for installation in tool-less rapid assembly systems. If the lamp gets dimmed, the colour temperature will decrease. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 460lm, Farbtemperatur: 3000 bis 1800K, Radiation angle: 38°, Adjustability: swivelling, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12461073	Applications
Stand:	26.11.2020 11:47	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	3000 - 1800
Colour	white
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Outer diameter	82 mm

Built-in diameter	68 mm
Built-in depth	38 mm
Current	350 mA
Luminous flux	460 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Swivel angle	30 °
circuit type secondary side	series conduction