



LED-Einbaustrahler BB15, dimmbar, mit DALI-Konverter und Anschlussbox
Artikel-Nr. 41475073



Distance (m)	Beam Diameter (m)	Beam Area (m²)
1.0 m	0.710.6	1184.2
2.0 m	1.411.3	298.1
3.0 m	2.111.9	131.6
4.0 m	2.812.5	74.0
5.0 m	3.513.1	47.4

Ø (m) E0(0°) [lx]

LED-Einbaustrahler BB15, dimmbar, mit DALI-Konverter und Anschlussbox, weiß. In a compact design, for installation in tool-less rapid assembly systems. Set inkl. DALI-Konverter für 230 V-Netzspannung, Maße Konverter: L 110,5 x B 52 x H 22 mm. Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 640lm, Colour temperature: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: not adjustable, With operating gear, Type of dimming: DALI, .

Artikel-Nr.	41475073	Applications
Stand:	25.11.2020 19:12	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	3000
Colour	white
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Stainless steel / Aluminium / Glass
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	DALI

Outer diameter	82 mm
Built-in diameter	68 mm
Built-in depth	45 mm
voltage	230V AC 50Hz
Luminous flux	640 lm
IP protection class	IP54*
Protection class	II
Voltage type	AC
Adjustability	not adjustable
circuit type secondary side	parallel conduction