


recessed spot

Artikel-Nr. H2067.00



recessed spot, messing, round. In a compact design, for installation in tool-less rapid assembly systems. Inkl. Hochvoltbügel zur normgerechten Zugentlastung. Lamp holder: GZ10, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Brass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: max. 50W, amount of light sources / fittings: 1.0 Stk, Adjustability: swivelling, Type of dimming: other, .

| | |
|--------------------|------------------|
| Artikel-Nr. | H2067.00 |
| Stand: | 14.02.2021 20:40 |

| | |
|------------------------------------|-----------|
| Colour | brass |
| amount of light sources / fittings | 1 Qty |
| Type of dimming | other |
| Outer diameter | 76 mm |
| Built-in diameter | 68 mm |
| Built-in depth | 125 mm |
| material | Brass |
| version | GZ10 |
| Power | max. 50 W |

| | |
|-----------------------------|---------------------|
| voltage | 230V AC 50Hz |
| Lamp type | HV halogen lamp |
| circuit type secondary side | parallel conduction |
| IP protection class | IP20 |
| Protection class | II |
| Swivel angle | 25 ° |
| Voltage type | AC |
| Adjustability | swivelling |