



LED-Einbaustrahler set BB09, dimmbar, mit Rund-Konverter
Artikel-Nr. 40369073



Distance (m)	Beam Diameter (m)	Luminous Flux (lm)
1.0 m	0.710.6	1184.2
2.0 m	1.411.3	298.1
3.0 m	2.111.9	131.6
4.0 m	2.812.5	74.0
5.0 m	3.513.1	47.4

LED-Einbaustrahler set BB09, dimmbar mit Rund-Konverter, white. In a compact design, for installation in tool-less rapid assembly systems. set incl. driver for 230V. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 640lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: swivelling, With operating gear, Type of dimming: Phase cut-off, .

Artikel-Nr.	40369073	Applications
price	54.80 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	01.09.2020 23:10	GASTRONOMY
Discount group	Discount group 1	

colour of light	3000 K
Colour	white
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Stainless steel / Aluminium / Plastic
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	Phase cut-off

Outer diameter	82 mm
Built-in diameter	68 mm
Built-in depth	38 mm
voltage	230V AC 50Hz
Luminous flux	640 lm
IP protection class	IP20
Protection class	II
Voltage type	AC
Adjustability	swivelling
Swivel angle	25 °
circuit type secondary side	parallel conduction