


LED-System-Downlight COUPLED, IP44, rund

Artikel-Nr. 12630073



LED-System-Downlight COUPLED, IP44, rund, weiß. In a compact design, for installation in tool-less rapid assembly systems. Montage nur zzgl. Einputz- oder Einbaurahmen 82030170 oder 82032170 möglich. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, current: 500 mA, Power: 8,9W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 950lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 34°, Adjustability: not adjustable, without operating, Type of dimming: other, .

Artikel-Nr.	12630073	Applications
Stand:	26.11.2020 02:45	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	3000
Colour	white
Radiation angle	34 °
amount of light sources / fittings	1 Qty
material	Aluminium / Plastic
Power	8,9 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	other

Outer diameter	68 mm
Built-in depth	79 mm
Current	500 mA
Luminous flux	950 lm
IP protection class	IP44*
Protection class	III
Voltage type	DC
Adjustability	not adjustable
circuit type secondary side	series conduction