


LED-Lichtpunkt, IP43  
**Artikel-Nr. P3653B**



LED-Lichtpunkt IP43, chrome, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play 350mA, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP43\*, Protection class: (EN 61140) III, current: 350 mA, Power: 1W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 20lm, Radiation angle: 30°, Adjustability: not adjustable, .

<b>Artikel-Nr.</b>	<b>P3653B</b>	<b>Applications</b>
<b>price</b>	31.10 €	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY
<b>Stand:</b>	19.03.2020 22:14	GASTRONOMY

Energy efficiency class	special product *
colour of light	blau
Luminous flux	20 lm
Radiation angle	30 °
material	Aluminium / Plastic
version	Plug&Play
Colour	chrom
Power	1 W
Lamp type	LED

Built-in diameter	25 mm
Built-in depth	20 mm
current	350 mA
circuit type secondary side	series conduction
IP protection class	IP43*
Protection class	III
Voltage type	DC
Adjustability	not adjustable