


LED-Einbaudownlight FUNIL
Artikel-Nr. 12241173

Licht.
 Für Generationen.



LED-Einbaudownlight FUNIL, white, round. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 500 mA, Power: 8,9 W, Luminous flux: 950.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 32.0 °, Adjustability: not adjustable, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A,

Artikel-Nr.	12241173	Applications
price	59.70 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 12:09	GASTRONOMY

colour of light	3000 K
Colour	white
Radiation angle	32 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
Power	8,9 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	other
Outer diameter	79 mm

Built-in diameter	68 mm
Built-in depth	63 mm
current	500 mA
Luminous flux	950 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
circuit type secondary side	series conduction