


recessed spot

**Artikel-Nr. 88662074**



recessed spot, weiß. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 40W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 4.510lm, Farbtemperatur: 3500K, Colour of light: white, Radiation angle: 36°, Adjustability: rotating and swivelling, With operating gear, Type of dimming: switchable, . This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>88662074</b>
<b>Stand:</b>	15.02.2021 20:11

colour of light	3500
Colour	white
Radiation angle	12 °
amount of light sources / fittings	1 Qty
material	Aluminium
Power	40 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	switchable

Outer diameter	180 mm
Built-in diameter	168 mm
Built-in depth	172 mm
voltage	230V AC 50Hz
IP protection class	IP20
Protection class	II
Adjustability	rotating and swivelling
Swivel angle	35 °
circuit type secondary side	parallel conduction