




recessed spot

**Artikel-Nr. 12295023**



recessed spot, chrom. In a compact design, for installation in tool-less rapid assembly systems. Einbaustrahler geeignet zur direkten Montage auf normalentflammbaren Baustoffen. Wärmedämmung zulässig. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 5,5W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 550lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 36°, Adjustability: swivelling, without operating, .

<b>Artikel-Nr.</b>	<b>12295023</b>	<b>Applications</b>
<b>Stand:</b>	25.11.2020 07:39	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY   GASTRONOMY

colour of light	3000
Colour	chrome
Radiation angle	36 °
amount of light sources / fittings	1 Qty
material	Aluminium / Steel / Plastic
version	Plug&Play
Power	5,5 W
Lamp type	LED
Colour rendering	CRI > 80

Built-in diameter	68 mm
Built-in depth	45 mm
Current	350 mA
Luminous flux	550 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Swivel angle	15 °
circuit type secondary side	series conduction