



## LED recessed spot set BB19, dim2warm, phase dimmable, incl. connection box



LED recessed spot set BB19, dim2warm, phase dimmable, incl. connection box, white, square. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Set including a converter for 230-V mains voltage, trailing-edge phase, Dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 460lm, Colour temperature: 3000 bis 1800K, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Type of dimming: Trailing-edge phase.

<b>Artikel-Nr.</b>	<b>39485073</b>		
<b>Stand:</b>	18.06.2021 07:02		
Colour of light	3000 - 1800 K	Type of dimming	Trailing-edge phase
Colour	White	Built-in diameter	68 mm
Length	82 mm	Installation depth	50 mm
Beam angle	38 °	Voltage	230V AC 50Hz
Amount of light sources / fittings	1 Qty	Degree of protection	IP20
Material	Aluminium / Glass / Plastic	Protection class	II
Power	6 W	Adjustability	Pivoted
Lamp	LED	Length	82 mm
Shipping	Incl. 3-pole connection box to connect to the 230-V mains voltage	Width	82 mm
Colour rendering	CRI > 80	Swivel angle	30 °
		Circuit type	Parallel conduction