




recessed spot

Artikel-Nr. 12286023



recessed spot, chrom, square. In a compact design, for installation in tool-less rapid assembly systems. Einbaustrahler geeignet zur direkten Montage auf normalentflammbaren Baustoffen. Wärmedämmung zulässig. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 5,5W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 550lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 36°, Adjustability: swivelling, without operating, Type of dimming: other, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12286023	Applications
Stand:	26.11.2020 00:28	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY GASTRONOMY

colour of light	3000
Colour	chrome
Radiation angle	36 °
amount of light sources / fittings	1 Qty
material	Aluminium / Steel / Plastic
version	Plug&Play
Power	5,5 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other
Outer diameter	95 mm

Built-in diameter	83 mm
Built-in depth	38 mm
Current	350 mA
Luminous flux	550 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
length	95 mm
Width	95 mm
Swivel angle	25 °
circuit type secondary side	series conduction