


LED-Einbaudownlight
Artikel-Nr. 12095263

Licht.
 Für Generationen.



LED-Einbaudownlight, titanium. In a compact design, for installation in tool-less rapid assembly systems. . Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 12V, Power: 2 W, Luminous flux: 120.0 lm, Colour of light: white, Radiation angle: 45.0 °, Energy efficiency class: A++ to A,

Artikel-Nr.	12095263	Applications
price	33.50 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 12:25	GASTRONOMY

colour of light	3000 K
Colour	titanium
Radiation angle	45 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
Power	2 W
Lamp type	LED
shipping	inkl. 2.000 mm Anschluss-
Colour rendering	CRI > 80

Built-in diameter	36 mm
Built-in depth	13 mm
voltage	12V
Luminous flux	120 lm
IP protection class	IP20
Protection class	III
Energy efficiency class	A++ to A
circuit type secondary side	parallel conduction