


recessed spot

Artikel-Nr. 88656073



recessed spot, weiß. In a compact design, for installation in tool-less rapid assembly systems. Zur optimalen Waren-Präsentation durch gleichmäßiges Lichtbild, in allen Sortimentsumgebungen geeignet. Energieeffizient und Verkaufsfördernd. Durch die hohe Variantenvielfalt ergibt sich ein einheitliches stimmiges Konzept für die ganzheitliche Beleuchtung. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 40W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 4.382lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 12°, Adjustability: rotating and swivelling, With operating gear, Type of dimming: switchable, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	88656073	Applications
Stand:	26.11.2020 09:12	SHOP RETAIL EDUCATION CULTURE

Radiation angle	12 °
colour of light	3000
Colour	weiß
Luminous flux	4,382 lm
amount of light sources / fittings	1 Qty
material	Aluminium
Power	40 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	switchable

Outer diameter	180 mm
Built-in diameter	168 mm
Built-in depth	172 mm
voltage	230V AC 50Hz
IP protection class	IP20
Protection class	II
Voltage type	AC
Adjustability	rotating and swivelling
Swivel angle	35 °
circuit type secondary side	parallel conduction