


LED-Einbaudownlight, IP44
Artikel-Nr. 12130023

Licht.
 Für Generationen.



LED-Einbaudownlight IP44, chrome, square. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Die-cast aluminium / Plastic, IP protection class: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, voltage: 12V, Power: 7,5 W, Luminous flux: 525.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 60.0 °, Adjustability: not adjustable, With operating gear: No, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

| | | |
|--------------------|------------------|---|
| Artikel-Nr. | 12130023 | Applications |
| price | 59.80 € | HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY |
| Stand: | 27.08.2019 11:42 | GASTRONOMY |

| | |
|---------------------------|------------------------------|
| colour of light | 3000 K |
| Colour | chrome |
| Radiation angle | 60 ° |
| amount of light sources / | 1 Qty |
| material | Die-cast aluminium / Plastic |
| Power | 7,5 W |
| Lamp type | LED |
| shipping | inkl. 2.000 mm Anschluss- |
| Colour rendering | CRI > 80 |
| Built-in diameter | 79 mm |
| Built-in depth | 14 mm |

| | |
|-----------------------------|---------------------|
| voltage | 12V |
| Luminous flux | 525 lm |
| IP protection class | IP44* |
| Protection class | III |
| Voltage type | DC |
| Adjustability | not adjustable |
| Energy efficiency class | A++ to A |
| Length | 85 mm |
| Width | 85 mm |
| Height-depth | 3.0 mm |
| circuit type secondary side | parallel conduction |