


recessed spot

Artikel-Nr. 124 19 173

Licht.
Für Generationen.



recessed spot, white. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 500 mA, Power: 2 x 9,3 W, amount of light sources / fittings: 2.0 Stk, Luminous flux: 1400.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 32.0 °, Adjustability: rotating and swivelling, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A,

Artikel-Nr.	124 19 173	Applications
price	171.80 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	27.08.2019 16:08	GASTRONOMY

colour of light	3000 K
Colour	white
Radiation angle	32 °
amount of light sources /	2 Qty
material	Aluminium / Plastic
Lichtstrom	2 x 700 lm
Power	2 x 9,3 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	other
Built-in depth	60 mm

current	500 mA
Luminous flux	1,400 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	rotating and swivelling
Energy efficiency class	A++ to A
Length	208 mm
Width	105 mm
Swivel angle	40 °
circuit type secondary side	series conduction