


LED-Wandanbauleuchte, IP54
Artikel-Nr. 60110103

Licht.
 Für Generationen.



LED-Wandanbauleuchte, IP54, graphite. Surface mounting, Wall-mounted. Lichtaustritt direkt und indirekt. Wandanbauleuchte mit schraubenlos übergeschobenem Außen-gehäuse. Jeweils zwei Klappen ober- und unterseitig zum variabel einstellbaren Lichtaustritt des jeweiligen Lichtkegels. Abstrahlwinkel 2 x max. 100°. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Wall-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 2 x 3 W, amount of light sources / fittings: 2.0 Stk, Luminous flux: 150.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 100.0 °, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A,

Artikel-Nr.	60110103
price	219.00 €
Stand:	28.08.2019 11:40

colour of light	3000 K
Colour	graphite
Radiation angle	100 °
amount of light sources /	2 Qty
material	Aluminium / Glass
Lichtstrom	2 x 75 lm
Power	2 x 3 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss
Colour rendering	CRI > 80
Type of dimming	switchable

voltage	230V AC 50Hz
Luminous flux	150 lm
IP protection class	IP54
Protection class	I
Voltage type	AC
Energy efficiency class	A++ to A
Length	180 mm
Width	65 mm
Height-depth	150.0 mm
circuit type secondary side	parallel conduction