



LED-Panel 620 x 620 mm
Artikel-Nr. 12088003

Licht.
 Für Generationen.



Ø (m)	E00(°)	[lx]
1.0 m	2.1	1866.6
2.0 m	4.2	466.6
3.0 m	6.3	207.4
4.0 m	8.4	116.7
5.0 m	10.5	74.7

LED-Panel 620 x 620 mm, white. In a compact design, for installation in tool-less rapid assembly systems. set incl. driver for 230V. Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Polycarbonate, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 42 W, Luminous flux: 4380.0 lm, Radiation angle: 120.0 °, Energy efficiency class: A++ to A,

Artikel-Nr.	12088003	Applications
price	119.00 €	INDUSTRY CRAFT OFFICE COMMUNICATION SHOP
Stand:	27.08.2019 11:17	RETAIL HOTEL INDUSTRY GASTRONOMY

colour of light	3000 K
Colour	white
Radiation angle	120 °
amount of light sources /	1 Qty
material	Aluminium / Polycarbonate
Power	42 W
Lamp type	LED
shipping	inkl. mikroprismatischer Ab-

Colour rendering	CRI > 80
glare evaluation	UGR < 19
Built-in depth	12 mm
voltage	230V AC 50Hz
IP protection class	IP20
Protection class	II
Energy efficiency class	A++ to A
circuit type secondary side	parallel conduction