



## LED-Einlege-Panel 620 x 620 mm

### Artikel-Nr. 12088003



1.0 m	2.1	1866.6
2.0 m	4.2	466.6
3.0 m	6.3	207.4
4.0 m	8.4	116.7
5.0 m	10.5	74.7
Ø (m)		E0(0°) [lx]

LED-Einlege-Panel 620 x 620 mm, weiß. In a compact design, for installation in tool-less rapid assembly systems. set incl. driver for 230V. Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Polycarbonate, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 42W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 4.380lm, Farbtemperatur: 3000K, Radiation angle: 120°, .

<b>Artikel-Nr.</b>	<b>12088003</b>	<b>Applications</b>
<b>Stand:</b>	26.11.2020 09:58	INDUSTRY   CRAFT OFFICE   COMMUNICATION SHOP   RE-TAIL HOTEL INDUSTRY   GASTRONOMY

colour of light	3000
Colour	white
Radiation angle	120 °
amount of light sources / fittings	1 Qty
material	Aluminium / Polycarbonate
Power	42 W
Lamp type	LED
shipping	inkl. mikroprismatischer Abdeckung

Colour rendering	CRI > 80
glare evaluation	UGR < 19
Built-in depth	12 mm
voltage	230V AC 50Hz
IP protection class	IP20
Protection class	II
circuit type secondary side	parallel conduction