




LED-Einbaudownlight V4A IP54
Artikel-Nr. 13005223



LED-Einbaudownlight V4A IP54, stainless steel. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play 350mA, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP54*, Protection class: (EN 61140) III, current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 577lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: not adjustable, without operating, Type of dimming: other, . Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

| | | |
|--------------------|------------------|---|
| Artikel-Nr. | 13005223 | Applications |
| price | 106.40 € | HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY |
| Stand: | 20.03.2020 19:21 | GASTRONOMY |

| | |
|--------------------------------|-------------------------------|
| colour of light | 3000 K |
| Colour | stainless steel |
| Radiation angle | 38 ° |
| amount of light sources / fit- | 1 Qty |
| material | Stainless steel / Aluminium / |
| version | Plug&Play |
| Power | 6 W |
| Lamp type | LED |
| Colour rendering | CRI > 80 |
| Type of dimming | other |
| Built-in diameter | 68 mm |
| Built-in depth | 45 mm |

| | |
|-----------------------------|-------------------|
| current | 350 mA |
| Luminous flux | 577 lm |
| IP protection class | IP54* |
| Protection class | III |
| Voltage type | DC |
| Circlip | without circlip |
| Adjustability | not adjustable |
| Energy efficiency class | A++ to A |
| Length | 82 mm |
| Width | 82 mm |
| circuit type secondary side | series conduction |