


LED-Pendelprofileuchte BIRO60, mikroprismatische Abdeckung
Artikel-Nr. 77201694



LED-Pendelprofileuchte BIRO60, mikroprismatische Abdeckung, silver. Surface mounting, Ceiling-mounted. Optik: Mikroprismen
 Pendellänge: max. 1.500 mm, Gewicht: 2,5 kg. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 27W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 3.386lm, Farbtemperatur: 4000K, Colour of light: white, Radiation angle: 80°, With operating gear, Type of dimming: switchable, .

Artikel-Nr.	77201694
price	398.00 €
Stand:	18.03.2020 23:23

colour of light	4000 K
Colour	silver
Radiation angle	80 °
amount of light sources / fit-	1 Qty
material	Aluminium / Steel / Plastic
Power	27 W
Lamp type	LED
Colour rendering	CRI > 80
glare evaluation	UGR < 19
Type of dimming	switchable
voltage	230V AC 50Hz

Luminous flux	3,386 lm
IP protection class	IP20
Protection class	I
Voltage type	AC
Energy efficiency class	A++ to A
Length	1155 mm
Width	60 mm
Height	78 mm
circuit type secondary side	parallel conduction
Pendulum length max.	1,500 mm
Pendulum length min.	150 mm