




recessed spot

Artikel-Nr. 12486023



recessed spot, chrome, square. In a compact design, for installation in tool-less rapid assembly systems. Wird die Leuchte gedimmt, verringert sich die Farbtemperatur. Einbaustrahler geeignet zur direkten Montage auf normalentflammbaren Baustoffen. Wärmedämmung zulässig. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 5,5W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 550lm, Farbtemperatur: 3000 bis 1800K, Radiation angle: 36°, Adjustability: swivelling, without operating, Type of dimming: other, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12486023	Applications
price	73.30 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	02.09.2020 02:16	GASTRONOMY
Discount group	Discount group 1	

colour of light	3000 - 1800 K
Colour	chrome
Radiation angle	36 °
amount of light sources / fittings	1 Qty
material	Aluminium / Steel / Plastic
version	Plug&Play
Power	5,5 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other
Built-in diameter	83 mm

Built-in depth	38 mm
Current	350 mA
Luminous flux	550 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Length	95 mm
Width	95 mm
Swivel angle	25 °
circuit type secondary side	series conduction