


LED-Anbauprofilleuchte BIRO60, mikroprismatische Abdeckung
Artikel-Nr. 77101694

Licht.
 Für Generationen.



LED-Anbauprofilleuchte BIRO60, mikroprismatische Abdeckung, silver. Surface mounting, Ceiling-mounted. LED-Profilleuchte mit mikroprismatischer Abdeckung. Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 27 W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 3386.0 lm, colour of light: 4000 K, Colour of light: white, Radiation angle: 80.0 °, Adjustability: not adjustable, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A,

Artikel-Nr.	77101694
price	319.00 €
Stand:	28.08.2019 12:28

colour of light	4000 K
Colour	silver
Radiation angle	80 °
amount of light sources /	1 Qty
material	Aluminium / Steel / Plastic
Power	27 W
Lamp type	LED
Colour rendering	CRI > 80
glare evaluation	UGR < 19
Type of dimming	switchable
voltage	230V AC 50Hz

Luminous flux	3,386 lm
IP protection class	IP20
Protection class	I
Voltage type	AC
Adjustability	not adjustable
Energy efficiency class	A++ to A
Length	1155 mm
Width	60 mm
Height-depth	80.0 mm
circuit type secondary side	parallel conduction