




recessed spot

Artikel-Nr. 12262643



recessed spot, titanium, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 7W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 740lm, Farbtemperatur: 2700K, Colour of light: white, Radiation angle: 38°, Adjustability: swivelling, without operating, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12262643	Applications
price	59.00 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	20.03.2020 05:20	GASTRONOMY

colour of light	2700 K
Colour	titanium
Radiation angle	38 °
amount of light sources / fit-	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	7 W
Lamp type	LED
Colour rendering	CRI > 80
Built-in diameter	68 mm
Built-in depth	36 mm

current	350 mA
Luminous flux	740 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Energy efficiency class	A++ to A
Length	82 mm
Width	82 mm
Swivel angle	30 °
circuit type secondary side	series conduction