




LED-Einbaudownlight, dim2warm

**Artikel-Nr. 12116073**

Licht.  
Für Generationen.



LED-Einbaudownlight dim2warm, white, round. In a compact design, for installation in tool-less rapid assembly systems. Wird die Leuchte gedimmt, verringert sich die Farbtemperatur. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 12 W, Luminous flux: 930.0 lm, colour of light: 3000 to 1800 K, Radiation angle: 24.0 °, Adjustability: not adjustable, With operating gear: No, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>12116073</b>
<b>price</b>	93.00 €
<b>Stand:</b>	27.08.2019 11:00

colour of light	3000 - 1800 K
Colour	white
Radiation angle	24 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	12 W
Lamp type	LED
Colour rendering	CRI > 90
Outer diameter	82 mm

Built-in diameter	74 mm
Built-in depth	48 mm
current	350 mA
Luminous flux	930 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
Energy efficiency class	A++ to A
circuit type secondary side	series conduction