




LED-Einputzstrahler, 2-fach, rahmenlos
Artikel-Nr. 13458003

Licht.
 Für Generationen.



LED-Einputzstrahler, 2-fach, rahmenlos, white. In a compact design, for installation in tool-less rapid assembly systems. .
 Lamp holder: Plug&Play 350mA, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Plaster / Cast aluminium / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: je 6 W, amount of light sources / fittings: 2.0 Stk, Luminous flux: 1280.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 38.0 °, Adjustability: swivelling, With operating gear: No, Type of dimming: other, Energy efficiency class: A++ to A, Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

Artikel-Nr.	13458003	Applications
price	193.10 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	16.07.2019 04:07	GASTRONOMY

colour of light	3000 K
Colour	white
Radiation angle	38 °
amount of light sources /	2 Qty
material	Plaster / Cast aluminium /
Lichtstrom	2 x 640 lm
Power	je 6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other
Built-in width	294 mm
Built-in length	175 mm

Built-in depth	115 mm
current	350 mA
Luminous flux	1,280 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	swivelling
Energy efficiency class	A++ to A
Length	170 mm
Width	288 mm
Swivel angle	25 °
circuit type secondary side	series conduction