

Einbaueinheit bündig 2-fach (oval) für LED-Module
Artikel-Nr. 45020170



Einbaueinheit für LED-Module, strukturweiß, other. In a compact design, for installation in tool-less rapid assembly systems. Einbaudurchmesser: 2x 82 mm version: without fitting, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 2x LED, max. 14W, amount of light sources / fittings: 2.0 Stk, without operating, Type of dimming: other, .

| | | |
|--------------------|------------------|--|
| Artikel-Nr. | 45020170 | Applications |
| Stand: | 26.11.2020 00:10 | HOME LIVING SPA WELLNESS HOTEL INDUSTRY GASTRONOMY |

| | |
|------------------------------------|--|
| Colour | white |
| amount of light sources / fittings | 2 Qty |
| material | Aluminium |
| version | without fitting |
| Power | 2 x LED, max. 14 W |
| shipping | inkl. Modulhalterungen bündig, schwenkbar (45020..), starr, IP44 (45021..) oder vertieft, schwenkbar (45022..) |

| | |
|---------------------|-----------------|
| Type of dimming | other |
| Built-in width | 164 mm |
| Built-in length | 82 mm |
| IP protection class | IP20 |
| Protection class | III |
| Circlip | without circlip |
| length | 175 mm |
| Width | 92 mm |
| Height-depth | 2.5 mm |